

Prorex - FPSH Flange Protectors Stud Holes 'Push-in'

- Standard in blue and black (depending on nominal pressure PN)
- Materiaal zwaar HD-PE met fixatie in de boutgaten
- According to EN 12351-A.3 / ASA / ANSI / BS 1560
- Flangesizes possible from **ANSI 1/2" to 12"**
- High impact protection during transport (protecting Raise Face—RF)
- Protection during stockage, transport, coating/painting, dirt, dust, animals.....
- Size indication on protection part

Flange protectors stud-hole

Partnumber	Pressure Nom. (in lbs.)	Normsize by ANSI	Colour	VPE
FPSH-1/2-150	125 / 150	1/2"	Blauw	800
FPSH-1/2-600	300 / 600	1/2"	Zwart	800
FPSH-3/4-150	125 / 150	3/4"	Blauw	800
FPSH-3/4-600	300 / 600	3/4"	Zwart	500
FPSH-1-150	125 / 150	1"	Blauw	600
FPSH-1-600	300 / 600	1"	Zwart	400
FPSH1-1/2-150	125 / 150	1-1/2"	Blauw	400
FPSH1-1/2-600	300 / 600	1-1/2"	Zwart	250
FPSH-2-150	125 / 150	2"	Blauw	250
FPSH-2-600	300 / 600	2"	Zwart	200
FPSH-3-150	125 / 150	3"	Blauw	200
FPSH-3-600	300 / 600	3"	Zwart	175
FPSH-4-150	125 / 150	4"	Blauw	200
FPSH-4-300	300	4"	Zwart	175
FPSH-6-150	125 / 150	6"	Blauw	125
FPSH-6-300	300	6"	Zwart	125
FPSH-8-150	150	8"	Blauw	100
FPSH-8-300	300	8"	Zwart	100
FPSH-10-150	150	10"	Blauw	60
FPSH-10-300	300	10"	Zwart	60
FPSH-12-150	150	12"	Blauw	40
FPSH-12-300	300	12"	Zwart	30

