

Seal-it – PA 6.6 high torque seal plugs - seal without O-ring

- Polyamide PA6.6 (**hoge torque** / high temperature)
- Temp. resistant continuous 120°C and intermit. to 200°C
- Acid and oil resistant
- Improved sealing properties
- Hexagonal (allen-)head for easy inside and outside fixing



Plugs for Gas-BSP thread

Part number	H mm	D mm	Thread	packing
SIP1/8	8,02	16,16	1/8"	2000
SIP1/4	9,88	18,12	1/4"	1000
SIP3/8	10,50	21,00	3/8"	1000
SIP1/2	10,97	25,19	1/2"	1000
SIP3/4	11,45	31,33	3/4"	500
SIP1	12,00	38,00	1"	500



Plugs for Metric thread

Part number	H mm	D mm	Thread	packing
SIPM10	8,5	16,0	M10	3000
SIPM12	11,5	18,5	M12	3000
SIPM14	11,50	20,0	M14	2000
SIPM16	8,0	21,5	M16	2000
SIPM18	7,5	22,5	M20	1000
SIPM20	7,5	23,5	M20	1000
SIPM22	8,0	25,0	M22	1000
SIPM24	8,5	28,0	M24	1000
SIPM26	11,5	31,0	M26	500

