


TempTex - High Temp protection TTV & TTI

- Type TTV — To assemble after repair/installation through high quality Velcro closure
- Type TTI — To assemble after repair/installation through wrapping
- Woven glassstructure, coated with high quality heat resistant silicone rubber and glassfibers.
- Designed to protect cables and hoses during high temperatures and occasional flames.
- Protects applications continuously up to 260°C and intermitted up to 1640°Celsius.
- Resistant to hydraulic fluids, oils, grease and petrols...
- TempTex is ideal to protect highly cost application at high temperatures.
- TempTex is additionally very much capable to isolate against loss of energie/temperature.
- Protections for the application but most importantly protection of persons/operators of high temperature applications or enviroments.
- Industry: Hydraulics, Piping, Auto-Motor-sports, Ovens, Cooling technics, Hightemp technics...



Partnumber	innerdia. (mm)	outerdia. (mm)	Meter per box (m)
TTV-25	25	32	15
TTV-32	32	39	15
TTV-38	38	45	15
TTV-44	44	51	15
TTV-51	51	58	15
TTV-57	57	64	15
TTV-64	64	71	15
TTV-70	70	77	15
TTV-76	76	83	15
TTV-83	83	90	15
TTV-89	89	96	15
TTV-95	95	102	15



Partnumber	Width (mm)	Thickness (mm)	Meter per box (m)
TTI-25	25	3	15
TTI-25	25	3	30
TTI-51	51	3	15
TTI-51	51	3	30
TTI-76	76	3	15
TTI-76	76	3	30
TTI-102	102	3	15
TTI-102	102	3	30
TTI-127	127	3	15
TTI-127	127	3	30



TST-254	25.4	0.5	11
TST-381	38.1	0.3	11

