

TieRex - Standard Cable-ties

- Material: Nylon 6.6
- Standard in Black (UV-resistant) and natural
- Inflammability class UL94V2
- Length 80 to 1500mm
- Width 2,5 to 12,7mm
- Other colours possible (see page [Cable ties coloured](#))
- Stock parts
- Temperature resistance -40°C to +85°C
- Also available in packs of 1.000 pcs.

Ref. Black	Ref. Natural	Length (mm)	Width (mm)	Packaging
TR08024B	TR08024N	80	2,4	100
TR10025B	TR10025N	100	2,5	100
TR12025B	TR12025N	120	2,5	100
TR14025B	TR15025N	140	2,5	100
TR16025B	TR16025N	160	2,5	100
TR20025B	TR20025N	200	2,5	100
TR14036B	TR28036N	140	3,6	100
TR15036B	TR15036N	150	3,6	100
TR20036B	TR20036N	200	3,6	100
TR30036B	TR30036N	292	3,6	100
TR37036B	TR37036N	370	3,6	100
TR12048B	TR12048N	120	4,8	100
TR16048B	TR16048N	160	4,8	100
TR18048B	TR18048N	180	4,8	100
TR20048B	TR20048N	200	4,8	100
TR25048B	TR25048N	250	4,8	100
TR28048B	TR28048N	280	4,8	100
TR30048B	TR30048N	300	4,8	100
TR37048B	TR37048N	370/368	4,8	100



TieRex - Standard Cable-ties

- Material: Nylon 6.6
- Standard in Black (UV-resistant) and natural
- Inflammability class UL94V2
- Length 80 to 1500mm
- Width 2,5 to 12,7mm
- Other colours possible (see page [Cable ties coloured](#))
- Stock parts
- Temperature resistance -40°C to +85°C
- Also available in packs of 1.000 pcs.

Ref. Black	Ref. Natural	Length (mm)	Width (mm)	Packaging
TR39048B	TR39048N	390	4,8	100
TR43048B	TR43048N	430	4,8	100
TR53048B	TR53048N	530	4,8	100
TR15076B	TR15076N	150	7,6	100
TR20076B	TR20076N	200	7,6	100
TR25076B	TR25076N	250	7,6	100
TR30076B	TR30076N	300	7,6	100
TR37076B	TR37076N	368/370	7,6	100
TR45076B	TR45076N	450	7,6	100
TR54076B	TR54076N	540	7,6	100
TR61576B	TR61576N	615	7,6	100
TR75076B	TR75076N	750	7,6	100
TR43090B	TR43090N	430	9,0	100
TR53090B	TR53090N	530	9,0	100
TR63090B	TR63090N	630	9,0	100
TR71090B	TR71090N	710	9,0	100
TR77590B	TR77590N	775	9,0	100



TieRex - Standard Cable-ties

- Material: Nylon 6.6
- Standard in Black (UV-resistant) and natural
- Inflammability class UL94V2
- Length 80 to 1500mm
- Width 2,5 to 12,7mm
- Other colours possible (see page [Cable ties coloured](#))
- Stock parts
- Temperature resistance -40°C to +85°C
- Also available in packs of 1.000 pcs.



Ref. Black	Ref. Natural	Length (mm)	Width (mm)	Packaging
TR83090B	TR83090N	830	9,0	100
TR92090B	TR92090N	920	9,0	100
TR102090B	TR102090N	1020	9,0	100
TR122090B	TR122090N	1220	9,0	100
TR153090B	TR153090N	1530	9,0	100
TR23012B	TR23012N	230	12,6	100
TR48012B	TR48012N	480	12,6	100
TR58012B	TR58012N	580	12,6	100
TR73012B	TR73012N	730	12,6	100
TR88012B	TR88012N	880	12,6	100
TR103012B	TR103012N	1030	12,6	100
Sizes may vary. Other sizes available on request!				

Our cable-ties are manufactured in first choice nylon (PA6.6)!

Contact-us for even more economical volume packagings!